

Sumter Coatings, Painting Tools



PL005



TTB002



EP03P



CR063



How much paint do I need?

Tank Size Gallons	Approx. Sq. Ft.	Gallons of Paint Needed
30,000	2,000	8
18,000	1,250	6
12,000	1,160	5
1,000	225	1
500	116	2 tanks per gallon
250	57	4 tanks per gallon

Part Number	Description
880W2203	Blued white alkyd enamel, workhorse of the industry. Custom colors available upon request. Covers in one coat. Slow-chalking. (S5)
880W2201	Silicone alkyd white. Provides long-lasting finish. Excellent gloss. Excellent color retention. Bright white. Custom colors available. Easily applied with brush, roller or spray. Covers up to 350 sq. ft. per gallon, dries in 6-12 hours. Use (889W1370) Epoxy Off White primer for best adhesion. (S7)
800W2685	Modified Silicone alkyd white. (S-6)
Satin Shield Enamels* (885 series) Over 60 colors.	Fast and easy. Quick-dry, one coat coverage. Eliminates the need for a separate primer coat. Corrosion-resistant. Excellent color holdout. Lead and chromate free. Designed with cylinders in mind. In extreme weather conditions, where salt and moisture are a concern, chose a Sumter undercoat for the best possible results.
Eniviro-Tuff Industrial Enamels* (886 Series) 15 colors	Great for accent dome colors. Built-in rust-inhibition. Excellent color retention and durability.
888S2006	High-grade aluminum in every gallon. Excellent elasticity. Can be rolled on. A rust-inhibitive primer and bright aluminum finish. Wears long with less tarnishing from weather. (1110)
888S2005	2 lbs. of aluminum in every gallon. Excellent workability with rollers. Perfect for bulk and storage tanks. (1000)
888S2007	Aluminum paint with high hiding power. Produces a tougher dry film. (1151)
888S2008	Aluminum paint, ready-to-use. Spray application. Dries in 10 minutes.
855D1373 - Gray 855G1368 - Gray Green 855W1370 - Off White	Rust-inhibitive primer. Excellent adhesion. Corrosion resistance. Gray, Gray Green, and Off White. (1373/1368/1370)
880N2209	One-coat phenolic compound, primer and finish in one. For cylinder bottoms. May be used for underground tanks and pipes. Apply by brush, roller or spray. (L122)
856X2210	Thinner for all Sumter Coatings paints. (XL Thinner)
PL005	Penetrol wetting agent. Daub or brush on wherever rust cannot be removed (hinges, cotter keys on domes). May also be mixed with paint to slow drying time.

*Contact inside sales for more information.

BC0003
BONNET
ON



KM-1009
EMPTY 5
GALLON
BUCKET



LCV16

Part No.	Description	Part No.	Description
BC0003	Bucket cover	EP03P	Extension pole (42", 3 piece)
TTB002	Tank trim brush (w/12" handle)	EX048	Extension pole (48" piece)
WB042	Wire brush (w/metal scraper)	TA072	Telescoping aluminum extension (6'-12')
BG0001	Bucket grid (w/dimple)	AP024	Aluminum extension pole (2'-4')
TR09K	Tank roller (handle only)	PS012	Production sandpaper (med. grade sheets)
LCV16	Poly/lambswool cover (for 9" roller)	SCR007	Springs (for contour rollers)
CR063	Contour roller (7" complete assembly)	KN006	Knurled nuts (for contour rollers)
CR006	Contour roller refill (for 7" assembly)	AX101	Mildewcide additive Ass-X (1 oz.)
RC09P	9" Economy roller cover	PSB11	Paint Strainer (for gallons)
		KM-1009	Empty 5 gallon bucket