

Dormont Connectors, Quick Connect Couplings

Bergquist

Dormont residential connectors are durable, flexible, and easy to install. Designed with built-in safety features, Supr-Safe connectors help prevent dangerous gas leaks and provide for a long and trouble-free service life.



1637NX12



bergquistinc.com | 800 537 7518

Stainless Steel Gas Appliance Connectors

3/8" ID / 1/2" OD with 1/2" female x 1/2" male		1/2" ID / 7/8" OD with 3/4" female x 3/4" male	
Length	Part No.	Length	Part No.
12"	1637NX12	12"	1650NX12
18"	1637NX18	18"	1650NX18
24"	1637NX24	24"	1650NX24
36"	1637NX36	36"	1650NX36
48"	1637NX48	48"	1650NX48
60"	1637NX60	60"	1650NX60

Super-Safe™ Connectors for Mobile Homes

Part No.	Description	Length
1675NPX24	3/4" I.D. / 1" O.D.	24"
1675NPX36	3/4" I.D. / 1" O.D.	36"

Dormont Black Appliance Connectors

Specifically engineered for High-Temperature applications such as gas logs, fireplace inserts, etc. Designed to reduce glare & hide the connector from view.

1/4" ID x 3/8" OD - 3/8" MPT x 1/2" FNPT	
Part #	Length
10-2132-12	12"
10-2132-18	18"
10-2132-24	24"
10-2132-36	36"
10-2132-48	48"



1675NPX24



Quick Connect permits instant disconnection and fast, easy connection to gas supply line without using tools. Simply pull back operating ring and the coupling springs apart and shuts off gas. For gas connection bring two parts together until they snap in place. Fusible link (thermal shutoff) cuts off gas flow in presence of fire.

Quick Connect Couplings

Part Number	Description
401111	1/4" Male Quick Connect Plug x 1/4" MPT
401148	Fill Plug FPOL x 1/4" Male Quik Disconnect for Filling CGA 810
401207	Sturgis brass plug 3/8 fpt x male quick connect
104088	1/2" FPT quick disconnect appliance connector, 5 PSI, female end only
401506	1/2" FPT quic disconnect plug end only
104089	3/4" FPT quick disconnect appliance connector, 5 PSI, female end only
401606	3/4" FPT quick disconnect plug end only