

Motors, Three Phase



bergquistinc.com | 800 537 7518



Three Phase Baldor Explosion Proof Motors

Part Number	H.P.	RPM	Volts	Frame	Full Load Amps	Weight
M7018T	1 1/2	3450	230/460	143T	2.1	42
M7042T-I	3	1725	230/460	182T	4.1	105
M7075T	3	3450	230/460	145T	4.1	69
M7044T-I	5	1725	230/460	184T	6.7	120
M7072T	5	3450	230/460	184T	5.6	85
M7047T-I	7 1/2	1725	230/460	213T	10.2	177
M7170T-I	10	1725	230/460	215T	14.2	225
M7174T	10	3450	230/460	215T	11.6	236
M7054T-I	15	1770	230/460	254T	18	347
M7056T-I	20	1760	230/460	256T	24	365
M7058T-I	25	1775	230/460	284T	30.8	454

Note: (I) truck loading facilities where motors may run intermittently. Also, applications where explosion-proof motors are installed outdoors, exposed to the environment, and may not be operated for extended periods of time.





BALDOR
MOTORS AND DRIVES

Single Phase Baldor Explosion Proof Motors

Part Number	H.P.	RPM	Volts	Frame	Fold Load Amps	Weight
VL5023A *	1	1725	115/230	56C	6.5	54
VL5024A *	1 1/2	1725	115/230	56C	8	76
L5030T	1 1/2	3450	115/230	143T	7.5	56
L5018	3	1725	115/230	215	15	152
L5028T	3	3450	115/230	184T	14.5	84
L5020	5	1725	230	215	21	166

* C faced motors for Blackmer pumps

Note: Corken F & FF model pumps use 3450 RPM



bergquistinc.com | 800 537 7518

Bergquist