

Copper and Coated Copper Tubing

Aluminum Tubing

COPPER TUBING



CT0650

Refrigeration Copper
Sold by outside diameter (O. D.)

| Part Number | O.D. Tube Size | Length |
|-------------|----------------|--------|
| CT0450 | 1/4" | 50' |
| CT0650 | 3/8" | 50' |
| CT06100 | 3/8" | 100' |
| CT0850 | 1/2" | 50' |
| CT08100 | 1/2" | 100' |
| CT1050 | 5/8" | 50' |
| CT10100 | 5/8" | 100' |

COATED COPPER TUBING



GT0650

Coated Refrigeration Copper
Sold by outside diameter (O.D.)

| Part Number | O.D. Tube Size | Length |
|-------------|----------------|--------|
| GT0650 | 3/8" | 50' |
| GT06100 | 3/8" | 100' |
| GT0850 | 1/2" | 50' |
| GT08100 | 1/2" | 100' |
| GT1050 | 5/8" | 50' |
| GT10100 | 5/8" | 100' |



bergquistinc.com | 800 537 7518

Type K Copper
Sold by inside diameter (I. D.)

| Part Number | I. D. Tube Size | Length |
|-------------|-----------------|--------|
| KT0460 | 3/8" | 60' |
| KT04100 | 3/8" | 100' |
| KT0660 | 1/2" | 60' |
| KT06100 | 1/2" | 100' |
| KT0860 | 5/8" | 60' |
| KT08100 | 5/8" | 100' |

Coated L Copper
Sold by inside diameter (I. D.)



| Part Number | I.D. Tube Size | Length |
|-------------|----------------|--------|
| GTL0460 | 1/4" | 60' |
| GTL04100 | 1/4" | 100' |
| GTL0660 | 3/8" | 60' |
| GTL06100 | 3/8" | 100' |
| GTL0860 | 1/2" | 60' |
| GTL08100 | 1/2" | 100' |

Type L Copper
Sold by inside diameter (I. D.)

| Part Number | I. D. Tube Size | Length |
|-------------|-----------------|--------|
| LT0460 | 3/8" | 60' |
| LT04100 | 3/8" | 100' |
| LT0660 | 1/2" | 60' |
| LT06100 | 1/2" | 100' |
| LT0860 | 5/8" | 60' |
| LT08100 | 5/8" | 100' |

ALUMINUM TUBING

Aluminum Tubing
Sold by outside diameter (O. D.)
Full rolls only.

| Part Number | O.D. Tube Size | Length |
|-------------|----------------|--------|
| AL0250 | 1/8" | 50' |
| AL0450 | 1/4" | 50' |
| AL0650 | 3/8" | 50' |

Dormont Connectors, Quick Connect Couplings

Bergquist

Dormont residential connectors are durable, flexible, and easy to install. Designed with built-in safety features, Supr-Safe connectors help prevent dangerous gas leaks and provide for a long and trouble-free service life.



1637NX12



bergquistinc.com | 800 537 7518

Stainless Steel Gas Appliance Connectors

| 3/8" ID / 1/2" OD with 1/2" female x 1/2" male | | 1/2" ID / 7/8" OD with 3/4" female x 3/4" male | |
|--|----------|--|----------|
| Length | Part No. | Length | Part No. |
| 12" | 1637NX12 | 12" | 1650NX12 |
| 18" | 1637NX18 | 18" | 1650NX18 |
| 24" | 1637NX24 | 24" | 1650NX24 |
| 36" | 1637NX36 | 36" | 1650NX36 |
| 48" | 1637NX48 | 48" | 1650NX48 |
| 60" | 1637NX60 | 60" | 1650NX60 |

Super-Safe™ Connectors for Mobile Homes

| Part No. | Description | Length |
|-----------|---------------------|--------|
| 1675NPX24 | 3/4" I.D. / 1" O.D. | 24" |
| 1675NPX36 | 3/4" I.D. / 1" O.D. | 36" |

Dormont Black Appliance Connectors

Specifically engineered for High-Temperature applications such as gas logs, fireplace inserts, etc. Designed to reduce glare & hide the connector from view.

| 1/4" ID x 3/8" OD - 3/8" MPT x 1/2" FNPT | |
|--|--------|
| Part # | Length |
| 10-2132-12 | 12" |
| 10-2132-18 | 18" |
| 10-2132-24 | 24" |
| 10-2132-36 | 36" |
| 10-2132-48 | 48" |



1675NPX24



Quick Connect permits instant disconnection and fast, easy connection to gas supply line without using tools. Simply pull back operating ring and the coupling springs apart and shuts off gas. For gas connection bring two parts together until they snap in place. Fusible link (thermal shutoff) cuts off gas flow in presence of fire.

Quick Connect Couplings

| Part Number | Description |
|-------------|---|
| 401111 | 1/4" Male Quick Connect Plug x 1/4" MPT |
| 401148 | Fill Plug FPOL x 1/4" Male Quik Disconnect for Filling CGA 810 |
| 401207 | Sturgis brass plug 3/8 fpt x male quick connect |
| 104088 | 1/2" FPT quick disconnect appliance connector, 5 PSI, female end only |
| 401506 | 1/2" FPT quic disconnect plug end only |
| 104089 | 3/4" FPT quick disconnect appliance connector, 5 PSI, female end only |
| 401606 | 3/4" FPT quick disconnect plug end only |