

Parker LP Gas Hose...7132 Series
 Heavy duty, flexible, for liquid or vapor transfer,
 350 psig working pressure, black neoprene cover, continuous
 labeling, UL Listed
 Hose is available in cut lengths (by the foot), or
 in reel lengths.
 Order by inside diameter.



Propane Hose

Part Number	Nose I. D.	Hose O. D.	# of Braids	Ft/Reel *
HP04	1/4"	.58"	2	350'/700'
HP06	3/8"	.75"	2	600'
HP08	1/2"	.94"	2	500'
HP12	3/4"	1.25"	2	350'
HP16	1"	1.50"	2	250'
HP20	1 1/4"	1.87"	2	150'
HP24	1 1/2"	2.18"	3	150'
HP32	2"	2.75"	3	100'

*Estimated - some reels may be different lengths.

HP04 REEL



bergquistinc.com | 800 537 7518

Note: Rubber hose is pin pricked the length of the hose to allow for natural permeation of LP Gas through the cover. This may appear as bubbles when the hose is wet or sitting in water.

Crimped-on ends are available on any length of hose.

Testing & Certification available... We will pressure test (nitrogen tested at 420 psi, unless specified otherwise) and send a 'certification sheet' with the hose.

PARKER CRIMPED ON ENDS

Crimped-on Hose Ends

Part Number	Hose Size	Hose End
4NP	1/4" I.D.	1/4" MNPT
HY04-04FA	1/4" I.D.	1/4" Female Flare
6NP	3/8" I.D.	3/8" MNPT
HY06-06FA	3/8" I.D.	3/8" Female Flare
8NP	1/2" I.D.	1/2" MPT
HY08-08FA	1/2" I.D.	1/2" Female Flare
12NP	3/4" I.D.	3/4" MNPT
16NP	1" I.D.	1" MNPT
20NP	1 1/4" I.D.	1 1/4" MNPT
24NP	1 1/2" I.D.	1 1/2" MNPT
32NP	2" I.D.	2" MNPT

PARKER RUBBER FLEX CONNECTORS

Rubber Flex Connectors

Hose Size	Coupling Length	Minimum Overall Length
1/2" ID	2 7/8"	9"
3/4" ID	3"	9"
1" ID	3 1/2"	10"
1 1/4" ID	4"	12"
1 1/2" ID	4"	12"
2" ID	5 1/2"	12"



Custom made and certified rubber flex connectors. Maximum length available is 36" - see table for minimum lengths.