

Stencil Ink , Decals and Signs



3" TYPE N



RIO PAD



S-4

Diagraph Stenciling Ink and Accessories

Part Number	Description
3" Type N	3" roller assembly complete
Type N Rep Roller	3" replacement roller
RIO Cond	Roll It On conditioner
RIO Pads	Roll It On ink pads
S-1	Black ink - quart
S-4	Red ink - quart
S-6	Blue ink - quart

Many colors available.
Price varies with color.



DECALS, SIGNS AND LABELS



PIII



VI28



RIN LABEL

Cylinder Size	Material	Cylinder I.D. (in.)	Cylinder Water Capacity (lb.)	Recommended Dip Tube Length (in.)
6.25"	Steel	6.9	18.2	3.2
8"	Steel	7.6	13.9	3.6
10"	Steel	9.9	26.1	3.6
12"	Steel	8.9	24.2	3.6
12"	Steel	12.0	24.2	3.6
11.25"	Steel	12.0	25.1	3.2
20"	Steel	12.0	47.6	4.0
20"	Steel	12.0	49.7	4.0
30"	Steel	12.0	71.9	4.8
40"	Steel	12.0	98.3	6.0
60"	Aluminum	6.9	15.6	4.8
100"	Aluminum	10.0	23.6	4.8
200"	Aluminum	12.0	47.6	4.8
300"	Aluminum	12.0	71.9	4.8
400"	Aluminum	12.0	98.3	7.0

Notes:
1. This table contains the approximate load maximum (LDM) and gross dip tube length to be used for retrofitting cylinders with OPD collar manufacturing or retrofitting prevention device. This table does not apply to cylinders designed or manufactured after 1/1/01.
2. Requirement: If the dip tube length (LDM) is outside the cylinder does not appear in the above table, use the next smaller dip tube length in the table. Example: When the dip tube length is 4.5 in. in the table, use a 4.0 in. dip tube for the retrofit.
3. The dip tube length is not stamped on the cylinder, contact the manufacturer for the recommended dip tube length.

P-114



PMICH

