

SUMTER COATINGS/ PAINTING TOOLS

How much paint do I need?

Tank Size Gallons	Approx. Sq. Ft.	Gallons of Paint Needed
30,000	2,000	8
18,000	1,250	6
12,000	1,160	5
1,000	225	1
500	116	2 tanks per gallon
250	57	4 tanks per gallon



Sumter Coatings



Part Number	Description
880W2203	Blued white alkyd enamel, workhorse of the industry. Custom colors available upon request. Covers in one coat. Slow-chalking. (S-5)
880W2201	Silicone alkyd white. Provides long lasting finish. Excellent gloss. Excellent color retention. Bright white. Custom colors available. Easily applied with brush, roller or spray. Covers up to 350 sq.ft. per gallon, dries in 6-12 hrs. Use (889W1370) Epoxy Off White primer for best adhesion. (S-7)
Satin Shield Enamels* (885 series) Over 60 colors.	Fast & easy. Quick dry, one coat coverage. Eliminates the need for a separate primer coat. Corrosion resistant. Excellent color holdout. Lead and chromate free. Designed with cylinders in mind. In extreme weather conditions; where salt and moisture are a concern, choose a Sumter undercoat, for the best possible results.
Enviro-Tuff Industrial Enamels* (886 series) 15 colors.	Great for accent dome colors. Built-in rust-inhibition. Excellent color retention and durability.
888S2206	High grade of aluminum in every gallon. Excellent elasticity. Can be rolled on. A rust-inhibitive primer and bright aluminum finish. Wears long with less tarnishing from weather. (1110)
888S2205	2 lbs. of aluminum in every gallon. Excellent workability with rollers. Perfect for bulk and storage tanks. (1000)
888S2207	Aluminum paint with high hiding power and produces a tougher dry film. (1151)
888S2208	Aluminum paint - ready to use. Spray application. Dries in 10 minutes. (1140)
855D1373 - Gray 855G1368 - Gray Green 855W1370 - Off White	Rust inhibitive primer. Excellent adhesion. Corrosion resistance. Gray, gray-green, and off-white. (1373 / 1368 / 1370)
880N2209	One-coat phenolic compound - prime and finish in one. For cylinder bottoms. May be used for underground tanks and pipes. Apply by brush, roller or spray. (L122)
856X2210	Thinner for all Sumter Coatings paints. (XL Thinner)
PL005	Penetrol wetting agent. Daub or brush on wherever rust cannot be removed (hinges, cotter keys on domes). May also be mixed with paint to slow drying time.

* Contact inside sales for more information.

PL005



TTB002

EP03P

BC0003
BONNET
ON



KM-1009
EMPTY 5
GALLON
BUCKET



LCV16



CR063

Part No.	Description	Part No.	Description
BC003	Bucket cover	EX048	Extension pole (48" piece)
TTB002	Tank trim brush (w/12" handle)	TA072	Telescoping aluminum extension (6'-12')
WB042	Wire brush (w/metal scraper)	AP024	Aluminum extension pole (2'-4')
BG0001	Bucket grid (w/dimple)	PS012	Production sandpaper (med. grade sheets)
TR09K	Tank roller (handle only)	SCR007	Springs (for contour rollers)
LCV16	Lamb's wool cover (for 9" roller)	KN006	Knurled nuts (for contour rollers)
CR063	Contour roller (7" complete assembly)	PL005	Penetrol
CR006	Contour roller refill (for 7" assembly)	AX101	Mildewcide additive Ass-X (1 oz.)
EP03P	Extension pole (42", 3 piece)	PSB11	Paint Strainer (for gallons)
		KM-1009	Empty 5 gallon bucket